

Safety Data Sheet acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

1 Identification

- **Product name:** BlueLube Polishing Lubricant
- **Part number:** 90-205995 - 90-206010
- **Application of the substance / the mixture** Lubricant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Single Exposure 1

H370 Causes damage to the central nervous system and the eyes.



GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 1)

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

isopropyl alcohol
methyl isobutyl ketone
methyl alcohol

Hazard statements

Flammable liquid and vapor.
Causes serious eye irritation.
Suspected of causing cancer.
Causes damage to the central nervous system and the eyes.
May cause drowsiness or dizziness.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Hazardous components and components with occupational exposure limits:

64-17-5	ethyl alcohol ⚠ Flammable Liquids 2, H225	50-60%
67-63-0	isopropyl alcohol ⚠ Flammable Liquids 2, H225; ⚠ Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	20-30%
57-55-6	propylene glycol	10-20%
67-56-1	methyl alcohol ⚠ Flammable Liquids 2, H225; ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ⚠ Specific Target Organ Toxicity - Single Exposure 1, H370	3-<5%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 2)

108-10-1	methyl isobutyl ketone	1-5%
	 Flammable Liquids 2, H225;  Carcinogenicity 2, H351;  Acute Toxicity - Inhalation 4, H332; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H335	

· **Non-hazardous components:**

7732-18-5	water, distilled, conductivity or of similar purity	1-5%
-----------	---	------

· **Additional information:**

Water is a byproduct of ethyl alcohol.

The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Blindness

Unconsciousness

Breathing difficulty

Headache

Dizziness

Coughing

Nausea

Eye irritation

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:** Wear fully protective suit.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· **Environmental precautions:**

Do not allow to enter sewers/ surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 3)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:	
---	--

64-17-5 ethyl alcohol	
------------------------------	--

PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1000 ppm A3

67-63-0 isopropyl alcohol	
----------------------------------	--

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

57-55-6 propylene glycol	
---------------------------------	--

WEEL	Long-term value: 10 mg/m ³
------	---------------------------------------

67-56-1 methyl alcohol	
-------------------------------	--

PEL	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

108-10-1 methyl isobutyl ketone	
--	--

PEL	Long-term value: 410 mg/m ³ , 100 ppm
-----	--

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 4)

REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 75 ppm Long-term value: 20 ppm BEI, A3
· Ingredients with biological limit values:	
67-63-0 isopropyl alcohol	
BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
67-56-1 methyl alcohol	
BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
108-10-1 methyl isobutyl ketone	
BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· Breathing equipment: Use suitable respiratory protective device when high concentrations are present.**· Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eye protection:

Tightly sealed goggles

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 5)

9 Physical and chemical properties

<ul style="list-style-type: none"> · Information on basic physical and chemical properties · General Information · Appearance: <ul style="list-style-type: none"> Form: Liquid Color: Blue · Odor: Alcohol-like · Odor threshold: Not determined. 	
· pH-value:	Not determined.
· Change in condition <ul style="list-style-type: none"> Melting point/Melting range: Undetermined. Boiling point/Boiling range: 78 °C (172.4 °F) 	
· Flash point:	26.7 °C (80.1 °F) (Pensky-Martens Closed Cup)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	400 °C (752 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: <ul style="list-style-type: none"> Lower: 3.3 Vol % Upper: 19 Vol % 	
· Vapor pressure at 20 °C (68 °F):	66.7 hPa (50 mm Hg)
· Density at 20 °C (68 °F):	0.826 g/cm ³ (6.893 lbs/gal)
· Relative density	Not determined.
· Vapor density at 20 °C (68 °F)	1.5 (Air=1)
· Specific gravity:	0.8 (Water = 1)
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: <ul style="list-style-type: none"> Dynamic: Not determined. Kinematic: Not determined. 	
· Solvent content: <ul style="list-style-type: none"> Organic solvents: 96.1 % Water: 3.9 % VOC content: 96.07 % 	
· Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Keep away from open flames. - No smoking.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 6)

Keep away from heat.

Keep away from oxidising agents and acidic substances.

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide
- **Additional information:** Hazardous decomposition products may form during combustion.

* 11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****ATE (Acute Toxicity Estimate)**

Oral	LD50	2,597 mg/kg
Dermal	LD50	7,792 mg/kg
Inhalative	LC50/4 h	57.2-66 mg/l

64-17-5 ethyl alcohol

Oral	LD50	7,060 mg/kg (rat)
Dermal	LD50	15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	20,000 mg/l (rat)

67-63-0 isopropyl alcohol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

57-55-6 propylene glycol

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	20,800 mg/kg (rabbit)

67-56-1 methyl alcohol

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

108-10-1 methyl isobutyl ketone

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

· **Primary chemical irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer)**

64-17-5	ethyl alcohol	1
67-63-0	isopropyl alcohol	3
108-10-1	methyl isobutyl ketone	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 7)

<ul style="list-style-type: none"> · OSHA-Ca (Occupational Safety & Health Administration)
<ul style="list-style-type: none"> · None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	UN1987
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA 	Alcohols, n.o.s. (Ethanol, Isopropanol) ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL)) ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL (ISOPROPYL ALCOHOL))
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · IMDG, IATA 	
<div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 8)

· Packing group · DOT, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids 30 F-E,S-D A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations · Limited quantities (LQ) · Transport category · Tunnel restriction code	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L 5L 3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | isopropyl alcohol

67-56-1 | methyl alcohol

108-10-1 | methyl isobutyl ketone

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

67-56-1 | methyl alcohol

108-10-1 | methyl isobutyl ketone

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1 | methyl isobutyl ketone

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/01/2022

Version 4.0

Last revision 06/01/2022

Product name: BlueLube Polishing Lubricant

(Contd. of page 9)

· Chemicals known to cause developmental toxicity:	
64-17-5	ethyl alcohol
67-56-1	methyl alcohol
108-10-1	methyl isobutyl ketone

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Technical Services

· **Contact:** Pablo Mendoza

· **Last revision / supersedes version:** 06/01/2022 / 3.1

· **Supersedes date:** 06/16/2020

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**