

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

1 Identification

· Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

· Part number:

80-10045

80-11400 - 80-11810

80-30045 - 80-30060

80-40045 - 80-40065

80-50045 - 80-50065

- · Application of the substance / the mixture Abrasive blade
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Allied High Tech Products Inc.

2376 East Pacifica Place

USA-RANCHO DOMINGUEZ, CA 90220

USA

info@alliedhightech.com

- · Information department: Product safety department
- · Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the lung and the bones through prolonged or repeated exposure.



Skin Irrititation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Additional information:

All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 1)

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

trisodium hexafluoroaluminate

titanium dioxide

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

Causes damage to the lung and the bones through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

409-21-2	silicon carbide	50-60%	
13775-53-6	trisodium hexafluoroaluminate	10%	
	Specific Target Organ Toxicity - Repeated Exposure 1, H372; Aquatic Chronic 2, H411; Acute Toxicity - Inhalation 4, H332		
1309-37-1	diiron trioxide	5-10%	
7789-75-5	calcium fluoride	5-10%	
15096-52-3		2.5-<5%	
	Aquatic Chronic 2, H411; 🗘 Acute Toxicity - Inhalation 4, H332	-	
8002-74-2	Paraffin waxes and Hydrocarbon waxes	1-5%	
14075-53-7	potassium tetrafluoroborate	1-5%	
	Acute Toxicity - Oral 3, H301; (1) Skin Irrititation 2, H315; Eye Irritation 2A, H319	1	

(Contd. on page 3)

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

	0	Contd. of page 2)	
1305-62-0	calcium dihydroxide	≤1%	
	Skin Corrosion 1B, H314; Eye Damage 1, H318		
1305-78-8	calcium oxide	≤1%	
	Eye Damage 1, H318		
13463-67-7	titanium dioxide	0.1-≤1%	
	♦ Carcinogenicity 2, H351		
· Non-hazard	lous components:		
12068-85-8	Iron Disulphide	5-10%	
	Polymeric Resin (cured)	5-10%	
	Epoxy (cured)	5-10%	
1314-98-3	zinc sulphide	1-5%	

Additional information:

Product may contain many or all of the above ingredients.

The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Breathing difficulty

Eye irritation

Coughing

Dermatitis

Eye irritation

Dermatitis

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Keep away from ignition sources
- · Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

No special requirements.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the remaining constituent has no known exposure limits.

400.2	409-21-2 silicon carbide			
PEL	Long-term value: 15* 5** mg/m³			
	fibrous dust: *total dust **respirable fraction			
REL	Long-term value: 10* 5** mg/m³			
	*total dust **respirable fraction			
TLV	Long-term value: 10* 3** mg/m ³			
	fibrous dust:0.1 f/cc;, nonfibrous:*inh.,**resp.			
1309-	37-1 diiron trioxide			
PEL	Long-term value: 10* mg/m³			
	*Fume			
REL	Long-term value: 5 mg/m ³			
	Dust & fume, as Fe			
TLV	Long-term value: 5* mg/m ³			
	*as respirable fraction, A4			
7789-	75-5 calcium fluoride			
PEL	Long-term value: 2.5 mg/m ³			
	as F			
REL	Long-term value: 2.5 mg/m ³			
	as F			
TLV	Long-term value: 2.5 mg/m ³			
	as F, A4; BEI			
1509	15096-52-3 cryolite			
PEL	Long-term value: 2.5 mg/m ³			
	as F			
REL	Long-term value: 2.5 mg/m ³			
	as F			

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 4) 8002-74-2 Paraffin waxes and Hydrocarbon waxes REL | Long-term value: 2 mg/m³ TLV Long-term value: 2 mg/m³ 14075-53-7 potassium tetrafluoroborate PEL Long-term value: 2.5 mg/m³ as F REL | Long-term value: 2.5 mg/m³ as F TLV Long-term value: 2.5 mg/m³ as F, A4; BEI 1305-62-0 calcium dihydroxide PEL Long-term value: 15* 5** mg/m³ *total dust **respirable fraction REL | Long-term value: 5 mg/m³ TLV Long-term value: 5 mg/m³ 1305-78-8 calcium oxide PEL | Long-term value: 5 mg/m³ REL | Long-term value: 2 mg/m³ TLV Long-term value: 2 mg/m³ 13463-67-7 titanium dioxide PEL | Long-term value: 15* mg/m³ *total dust REL | See Pocket Guide App. A TLV Long-term value: (10) NIC-0.2* NIC-2.5** mg/m³ NIC: resp. fraction, *nanoscale, **finescale, A3 · Ingredients with biological limit values: 7789-75-5 calcium fluoride BEI 2 mg/L

Medium: urine Time: prior to shift

Parameter: Fluoride (background, nonspecific)

3 mg/L Medium: urine Time: end of shift

Parameter: Fluoride (background, nonspecific)

15096-52-3 cryolite

BEI 2 mg/L

Medium: urine Time: prior to shift

Parameter: Fluoride (background, nonspecific)

3 mg/L Medium: urine Time: end of shift

Parameter: Fluoride (background, nonspecific)

(Contd. on page 6)

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 5)

14075-53-7 potassium tetrafluoroborate

BEI 2 mg/L

Medium: urine Time: prior to shift

Parameter: Fluoride (background, nonspecific)

3 mg/L Medium: urine Time: end of shift

Parameter: Fluoride (background, nonspecific)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately. Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Leather gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eve protection:



Tightly sealed goggles

9 Physical and chemical properties

T 0 4				
· Information	on hasic	nhveical	and chemica	Inronerfies
mind mation	on basic	pmysicai	ana cnemica	i pi opci ucs

· General Information

· Appearance:

Form: Solid

Color: According to product specification

· Odor: Odorless
· Odor threshold: Not determined.

• pH-value: Not applicable.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not determined.

(Contd. on page 7)

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 6)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion: Product does not present an explosion hazard.	
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not applicable.
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Insoluble.
· Partition coefficient (n-octanol/water	r): Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC content: 0.00 %	
Solids content:	100.0 %
• Other information No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from oxidising agents and acidic substances.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Silicon oxides

Carbon monoxide and carbon dioxide

· Additional information: Hazardous decomposition products may form during combustion.

* 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
ATE (Acu	ATE (Acute Toxicity Estimate)				
Oral	LD50	6,500 mg/kg			
Inhalative	LC50/4 h	10 mg/l			

L					
Γ	409-21-2 silicon carbide				
ſ	Oral LD50 >2,000 mg/kg (rat)				
1	Dermal	LD50	>2,000 mg/kg (rat)		
ſ	13775-53-6 trisodium hexafluoroaluminate				
	Inhalative	LC50/4 h	1.5 mg/l (ATE)		

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 7)

		(Cond. of page 7)			
1309-37-1	1309-37-1 diiron trioxide				
Oral	LD50	>5,000 mg/kg (rat)			
7789-75-5	calcium f	luoride			
Oral	LD50	4,250 mg/kg (rat)			
15096-52-	3 cryolite				
Inhalative	LC50/4 h	1.5 mg/l (ATE)			
14075-53-	14075-53-7 potassium tetrafluoroborate				
Oral	Oral LD50 100 mg/kg (ATE)				
1305-62-0	calcium d	ihydroxide			
Oral	LD50	7,340 mg/kg (rat)			
13463-67-	13463-67-7 titanium dioxide				
Oral	LD50	>20,000 mg/kg (rat)			
Dermal	LD50	>10,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	>6.82 mg/l (rat)			
ъ.		+, , , , , , , , , , , , , , , , , , ,			

- · Primary chemical irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Abrasive eye irritant

Abrasive skin irritant

· Carcinogenic categories

· IARC (Inte	· IARC (International Agency for Research on Cancer)			
409-21-2	silicon carbide	2A		
1309-37-1	diiron trioxide	3		
7789-75-5	calcium fluoride	3		
14075-53-7	potassium tetrafluoroborate	3		
13463-67-7	titanium dioxide	2B		

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

2 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- **Ecotoxical effects:**
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 8)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
· Packing group · DOT, IMDG, IATA	not regulated	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARP the IBC Code	OL73/78 and Not applicable.	
· UN "Model Regulation":	not regulated	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

Sara		
Section 355 (extremely hazardous substances):		
None of the ingredients is listed.		
· Section 313 (Specific toxic chemical listings):		
1314-98-3 zinc sulphide		

- · TSCA (Toxic Substances Control Act):
- All components have the value ACTIVE.
- · Hazardous Air Pollutants

None of the ingredients is listed.

- **Proposition 65**
- Chemicals known to cause cancer:

13463-67-7 titanium dioxide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Printing date 06/01/2022 Version 3.0 Last revision 06/01/2022

Product name: Silicon Carbide Cut-Off & Wafering Blades, Resin Bond

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Technical Services

· Contact: Pablo Mendoza

· Last revision / supersedes version: 06/01/2022 / 2.1

· Supersedes date: 06/03/2020 · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Toxicity - Oral 3: Acute toxicity - Category 3

Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Skin Irrititation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.