



HIGH TECH PRODUCTS, INC.

2376 E. Pacifica Place Rancho Dominguez, CA 90220 (800) 675-1118 www.alliedhightech.com

# MATERIAL/CHEMICAL SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION				SECTION 3: HAZARDS IDENTIFICATION		
<b>Product Details</b> Product Name: EpoxySet Resin - Part A  Allied Item No.: 145-20000, -20005, -20015, -20025  Chemical Name: Modified Bisphenol A - Epichlorohydrin based Epoxy				Emergency Overview: Warning! Skin sensitizer. Potential respiratory tract sensitizer. Eye and skin irritant. Wash with soap and water thoroughly after use.  Hazard Statement: Combustible liquid. Keep liquid and vapor away from heat, sparks and flame. Vapors may accumulate and travel to distant ignition sources.  Primary Routes of Entry: Eye and skin contact, inhalation		
<b>Company Identification</b> Allied High Tech Products, Inc. 2376 East Pacifica Place Rancho Dominguez, CA 90220 (310) 635-2466  <b>Contact Point</b> Transportation for United States Chemtrec (800) 424-9300 * (202) 483-7616				<b>SECTION 4: FIRST AID MEASURES</b>		
				<b>Potential Health Effects</b>		<b>First Aid/ Medical Info.</b>
				Eye Contact:	May be severely irritating to the eyes. May cause corneal damage.	Immediately flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention.
				Skin Contact:	Extremely irritating to the skin and may cause damage.	Wash with soap and water.
<b>SECTION 2: COMPOSITION/INFORMATION ON INGREDIENT</b>						
Chemical Name	CAS No.	Exposure Limits in Air ACGIH TLV or TWA	Carcin. OSHA PEL Y/N			
Bisphenol A/ Epichlorohydrin Resin 85-90%	25068-38-6	NE	NE	Inhalation:	May cause irritation to the nose, throat and respiratory tract.	Remove to fresh air and provide oxygen if breathing is difficult. Seek medical attention.
N-Butyl Glycidyl Ether <15%	2426-08-06	25 ppm	25 ppm	Ingestion:	Product may be slightly toxic.	Induce vomiting only as directed by emergency personnel. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Seek medical attention.
				Note:		
				<b>SECTION 5: FIRE FIGHTING MEASURES</b>		
				Extinguishing Media: Alcohol foam, carbon dioxide, dry chemical or water.  Fire Fighting Instruction: Caution. Combustible. Do not enter confined fire space without full protective clothing and MSHA/NIOSH self-contained breathing apparatus with full facepiece. Cool fire exposed containers with water.  Special Hazards: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Vapors may accumulate and travel to distant ignition sources.		
				<b>SECTION 6: ACCIDENTAL RELEASE MEASURES</b>		
				Dike to prevent further movement. Contain with absorbent material such as clay, soil or any commercially available absorbent. Shovel reclaimed liquid and absorbent into recovery or salvage drums for disposal. Flush area with water to remove trace residue.		
Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.				<b>HMIS Ratings</b> Health: 3 Flammability: 2 Reactivity: 0		
Page 1 of 2:						

<b>SECTION 7: HANDLING &amp; STORAGE</b>	<b>SECTION 12: ECOLOGICAL INFORMATION</b>
<p>Handling: Avoid contact with skin and eyes. Avoid breathing vapors of heated material. Observe good housekeeping practices.</p> <p>Storage: Keep container closed when not in use.</p>	<p>NA</p>
<b>SECTION 8: EXPOSURE CONTROL &amp; PERSONAL PROTECTION</b>	<b>SECTION 13: DISPOSAL INFORMATION</b>
<p>Engineering Measures: General and/or local exhaust ventilation to control vapor concentration.</p> <p>Respiratory Protection: Use MSHA/NIOSH approved respiratory protection.</p> <p>Protective Gloves: Butyl or neoprene gloves and apron.</p> <p>Eye Protection: Safety glasses or chemical splash goggles.</p> <p>Other: Eye wash and shower facility should be available.</p>	<p>Dispose of waste material according to Federal, State and Local regulations.</p>
<b>SECTION 9: PHYSICAL &amp; CHEMICAL PROPERTIES</b>	<b>SECTION 14: TRANSPORT INFORMATION</b>
<p>Appearance: Liquid                  Odor: Ammoniacal odor                  Solubility: Soluble                  Boiling Point: 531°F (277°C)                  Melting Point: NA                  Flash Point: &gt;300°F (149°C) Setflash                  Vapor Pressure: &lt;.01 mm/Hg @ 68°F (20°C)                  Vapor Density: NA                  Evaporation Rate: &lt;0.01                  Specific Gravity: .98                  Flammable Limits LEL: NA                  Flammable Limits UEL: NA                  VOC Content: 27.47 grams/ltr when mixed</p>	<p>NA</p>
<b>SECTION 10: STABILITY &amp; REACTIVITY</b>	<b>SECTION 15: REGULATORY INFORMATION</b>
<p>Stability: Stable</p> <p>Conditions to Avoid/Incompatibles: Vigorous heating.</p> <p>Decomposition Products: Ethylenediamine, Diethylenetriamine, volatile amines and ammonia.</p> <p>Hazardous Polymerization: Will not occur.</p>	<p>SARA Title III Section 313 Information: This product does not contain any reportable chemicals.</p>
<b>SECTION 11: TOXICOLOGICAL INFORMATION</b>	<b>SECTION 16: OTHER INFORMATION</b>
<p>Primary Route(s) of Entry: Eye and skin contact, inhalation</p> <p>Toxicity: Oral LD50 -2.5 g/Kg (rat)                  Dermal LD50 - &gt;805mg/Kg (rabbit)                  Inhalation LC50 - NE</p>	<p><b>Legend</b>                  NAIF: No Applicable Information Found                  NA: Not Available/Applicable                  NE: None Established</p> <p><b>DISCLAIMER:</b> The above information and recommendations are believed accurate and reliable. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. ALLIED HIGH TECH PRODUCTS, INC. makes no warranty, either express or implied, as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer/distributor shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.</p>
<p>Page 2 of 2:</p>	<p>Form Prepared By: Allied High Tech Products, Inc. January 2011</p>



HIGH TECH PRODUCTS, INC.

2376 E. Pacifica Place Rancho Dominguez, CA 90220 (800) 675-1118 www.alliedhightech.com

## MATERIAL/CHEMICAL SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION				SECTION 3: HAZARDS IDENTIFICATION																									
<p><b>Product Details</b></p> <p>Product Name: EpoxySet Hardener - Part B</p> <p>Allied Item No.: 145-20000, -20010, -20020, -20030</p> <p>Chemical Name: Aliphatic Amine</p> <p><b>Company Identification</b>                      Allied High Tech Products, Inc.                      2376 East Pacifica Place                      Rancho Dominguez, CA 90220                      (310) 635-2466</p> <p><b>Contact Point</b>                      Transportation for United States                      Chemtrec (800) 424-9300 * (202) 483-7616</p>				<p>Emergency Overview: Causes eye and skin burns. Harmful and corrosive if swallowed. Harmful if inhaled or absorbed through skin. May cause asthma with possible long-term lung damage. May cause allergic skin reaction. Do not get in eyes, on skin or clothing. Avoid breathing vapor.</p> <p>Hazard Statement: None</p> <p>Primary Routes of Entry: Eye and skin contact, inhalation.</p>																									
SECTION 2: COMPOSITION/INFORMATION ON INGREDIENT				SECTION 4: FIRST AID MEASURES																									
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Chemical Name</th> <th style="text-align: left;">CAS No.</th> <th style="text-align: left;">Exposure Limits in Air ACGIH TLV or TWA</th> <th style="text-align: left;">Carcin. OSHA PEL Y/N</th> </tr> </thead> <tbody> <tr> <td>Triethylenetetramine 100%</td> <td>112-24-3</td> <td>NE</td> <td>NE</td> </tr> </tbody> </table>				Chemical Name	CAS No.	Exposure Limits in Air ACGIH TLV or TWA	Carcin. OSHA PEL Y/N	Triethylenetetramine 100%	112-24-3	NE	NE	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;"></th> <th style="text-align: center;">Potential Health Effects</th> <th style="text-align: center;">First Aid/ Medical Info.</th> </tr> </thead> <tbody> <tr> <td>Eye Contact:</td> <td>Corrosive to the eyes and may cause severe damage including blindness. Vapors may be irritating.</td> <td>Immediately flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention immediately.</td> </tr> <tr> <td>Skin Contact:</td> <td>Corrosive to the skin. May cause sensitization. May be toxic if absorbed through skin.</td> <td>Wash with soap and water. Remove contaminated clothing. Seek medical attention immediately.</td> </tr> <tr> <td>Inhalation:</td> <td>Severe irritation, difficult breathing and pulmonary sensitization.</td> <td>Remove to fresh air and provide oxygen if breathing is difficult. Seek medical attention.</td> </tr> <tr> <td>Ingestion:</td> <td>Harmful and corrosive and may cause severe and permanent damage to mouth, throat and stomach. May be moderately toxic if swallowed.</td> <td>Do NOT induce vomiting. Give one to two glasses of water unless victim is drowsy, convulsing or unconscious.</td> </tr> </tbody> </table> <p>Note: Induce vomiting only as directed by emergency personnel. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.                      Causes eye and skin burns. Harmful and corrosive if swallowed. Harmful if inhaled or absorbed through skin. May cause asthma with possible long-term lung damage. May cause allergic skin reaction.</p>				Potential Health Effects	First Aid/ Medical Info.	Eye Contact:	Corrosive to the eyes and may cause severe damage including blindness. Vapors may be irritating.	Immediately flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention immediately.	Skin Contact:	Corrosive to the skin. May cause sensitization. May be toxic if absorbed through skin.	Wash with soap and water. Remove contaminated clothing. Seek medical attention immediately.	Inhalation:	Severe irritation, difficult breathing and pulmonary sensitization.	Remove to fresh air and provide oxygen if breathing is difficult. Seek medical attention.	Ingestion:	Harmful and corrosive and may cause severe and permanent damage to mouth, throat and stomach. May be moderately toxic if swallowed.	Do NOT induce vomiting. Give one to two glasses of water unless victim is drowsy, convulsing or unconscious.
Chemical Name	CAS No.	Exposure Limits in Air ACGIH TLV or TWA	Carcin. OSHA PEL Y/N																										
Triethylenetetramine 100%	112-24-3	NE	NE																										
	Potential Health Effects	First Aid/ Medical Info.																											
Eye Contact:	Corrosive to the eyes and may cause severe damage including blindness. Vapors may be irritating.	Immediately flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention immediately.																											
Skin Contact:	Corrosive to the skin. May cause sensitization. May be toxic if absorbed through skin.	Wash with soap and water. Remove contaminated clothing. Seek medical attention immediately.																											
Inhalation:	Severe irritation, difficult breathing and pulmonary sensitization.	Remove to fresh air and provide oxygen if breathing is difficult. Seek medical attention.																											
Ingestion:	Harmful and corrosive and may cause severe and permanent damage to mouth, throat and stomach. May be moderately toxic if swallowed.	Do NOT induce vomiting. Give one to two glasses of water unless victim is drowsy, convulsing or unconscious.																											
SECTION 5: FIRE FIGHTING MEASURES				SECTION 6: ACCIDENTAL RELEASE MEASURES																									
<p>Ingredients are listed on the TSCA Inventory of Chemical Substances. Those not identified are non-hazardous.</p>				<p>Extinguishing Media: Alcohol foam, carbon dioxide, dry chemical or water.</p> <p>Fire Fighting Instruction: Caution. Combustible. Do not enter confined fire space without full protective clothing and MSHA/NIOSH self-contained breathing apparatus with full facepiece. Cool fire exposed containers with water.</p> <p>Special Hazards: During fire, oxides of nitrogen may be evolved.</p>																									
<p>Page 1 of 2:</p>				<p>Wear suitable protective gear. Flush with large amounts of water. Avoid discharge into sewers or waterways.</p>																									
<p><b>HMIS Ratings</b>                      Health: 3                      Flammability: 1                      Reactivity: 0</p>																													

<p><b>SECTION 7: HANDLING &amp; STORAGE</b></p>	<p><b>SECTION 12: ECOLOGICAL INFORMATION</b></p>
<p>Handling: Avoid contact with skin and eyes. Avoid breathing vapors of heated material. Observe good housekeeping practices.</p> <p>Storage: Keep container closed when not in use.</p>	<p>NA</p>
<p><b>SECTION 8: EXPOSURE CONTROL &amp; PERSONAL PROTECTION</b></p>	<p><b>SECTION 13: DISPOSAL INFORMATION</b></p>
<p>Engineering Measures: General and/or local exhaust ventilation to control vapor concentration.</p> <p>Respiratory Protection: Use MSHA/NIOSH approved respiratory protection.</p> <p>Protective Gloves: Butyl or neoprene gloves and apron.</p> <p>Eye Protection: Safety glasses or chemical splash goggles.</p> <p>Other: Eye wash and shower facility should be available.</p>	<p>Dispose of waste material according to Federal, State and Local regulations.</p>
<p><b>SECTION 9: PHYSICAL &amp; CHEMICAL PROPERTIES</b></p>	<p><b>SECTION 14: TRANSPORT INFORMATION</b></p>
<p>Appearance: Liquid                  Odor: Ammoniacal odor                  Solubility: Soluble                  Boiling Point: 531°F (277°C)                  Melting Point: NA                  Flash Point: &gt;300°F (149°C) Setflash                  Vapor Pressure: &lt;.01 mm/Hg @ 68°F (20°C)                  Vapor Density: NA                  Evaporation Rate: &lt;0.01                  Specific Gravity: .98                  Flammable Limits LEL: NA                  Flammable Limits UEL: NA                  VOC Content: 27.47 grams/ltr when mixed</p>	<p>DOT Shipping Name: Triethylenetetramine</p> <p>Corrosive Liquid NOS</p> <p>DOT Hazard Class: 8</p> <p>DOT Id Number: UN2259</p> <p>DOT Packing Group: II</p>
<p><b>SECTION 10: STABILITY &amp; REACTIVITY</b></p>	<p><b>SECTION 15: REGULATORY INFORMATION</b></p>
<p>Stability: Stable</p> <p>Conditions to Avoid/Incompatibles: Vigorous heating.</p> <p>Decomposition Products: Ethylenediamine, Diethylenetriamine, volatile amines and ammonia.</p> <p>Hazardous Polymerization: Will not occur.</p>	<p>SARA Title III Section 313 Information: This product does not contain any reportable chemicals.</p>
<p><b>SECTION 11: TOXICOLOGICAL INFORMATION</b></p>	<p><b>SECTION 16: OTHER INFORMATION</b></p>
<p>Primary Route(s) of Entry: Eye and skin contact, inhalation</p> <p>Toxicity: Oral LD50 -2.5 g/Kg (rat)                  Dermal LD50 - &gt;805mg/Kg (rabbit)                  Inhalation LC50 - NE</p>	<p><b>Legend</b>                  NAIF: No Applicable Information Found                  NA: Not Available/Applicable                  NE: None Established</p> <p><b>DISCLAIMER:</b> The above information and recommendations are believed accurate and reliable. Because it is not possible to anticipate all conditions of use, additional safety precautions may be required. ALLIED HIGH TECH PRODUCTS, INC. makes no warranty, either express or implied, as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer/distributor shall not be liable for damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.</p>
<p>Page 2 of 2:</p>	<p>Form Prepared By: Allied High Tech Products, Inc. January 2011</p>