

Page 1/9

Safety Data Sheet acc. to OSHA HCS

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

1 Identification

· Product name: Acrylic Tinting Concentrate

· Part number: 170-21000, 170-21005, 170-21010, 170-21015

· Application of the substance / the mixture

Tinting concentrate

Additive

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Allied High Tech Products Inc.

2376 East Pacifica Place

USA-RANCHO DOMINGUEZ, CA 90220

USA

info@alliedhightech.com

- · Information department: Product safety department
- · Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to the kidneys and the liver through prolonged or repeated exposure.



Acute Toxicity - Inhalation 4 H332 Harmful if inhaled. Skin Irrititation 2 H315 Causes skin irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: Acrylic Tinting Concentrate

(Contd. of page 1)

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labeling:

methyl methacrylate

N,N-dimethyl-p-toluidine

Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to the kidneys and the liver through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Product name: Acrylic Tinting Concentrate

(Contd. of page 2)

· Hazardous components and components with occupational exposure limits:	
80-62-6 methyl methacrylate	90-100%
Flammable Liquids 2, H225; Acute Toxicity - Inhalation 4, H332; Skin Irrititation 2, H315; Sensitization - 1, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	Skin
99-97-8 N,N-dimethyl-p-toluidine	0.1-≤1%
Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; Carcinogenicity 2, H351; Specific Target Organ Toxicity - Repeated Exposure 2, H373; Flammable Liquids 4, H227; Aquatic Chronic 3, H412	
· Non-hazardous components:	
Dye	≤1%

Additional information: The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Rinse out mouth and then drink plenty of water.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Breathing difficulty

Headache

Dizziness

Coughing

Allergic reactions

Nausea

Dermatitis

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: Acrylic Tinting Concentrate

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store at temperatures not exceeding 25°C.
- · Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from reducing agents.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Contro	of parameters
· Comp	onents with limit values that require monitoring at the workplace:
80-62-	6 methyl methacrylate
PEL	Long-term value: 410 mg/m³, 100 ppm
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm
	Long-term value: 205 mg/m³, 50 ppm
	DSEN, A4
99-97-	8 N,N-dimethyl-p-toluidine
WEEL	Long-term value: 0.5 ppm

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment: Use suitable respiratory protective device when high concentrations are present.

(Contd. on page 5)

Product name: Acrylic Tinting Concentrate

(Contd. of page 4)

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and ch	nemical properties
General Information	
· Appearance: Form:	T::1
Color:	Liquid According to product specification
· Odor:	Acrid
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-48 °C (-54.4 °F)
Boiling point/Boiling range:	101 °C (213.8 °F)
· Flash point:	11.5 °C (52.7 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C (806 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
· Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
· Density at 20 °C (68 °F):	0.94 g/cm³ (7.844 lbs/gal)
· Relative density	Not determined.
· Vapor density at 15.5 °C (59.9 °F)	3.5 (Air = 1)
· Specific gravity:	0.949 (Water = 1)
· Evaporation rate	3.1 (BuAc = 1)
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	1.6 g/l
· Partition coefficient (n-octanol/water	r): Not determined.

Product name: Acrylic Tinting Concentrate

(Contd. of page 5)

· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: VOC content:	0.00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Danger of polymerization.
- · Conditions to avoid

Protect from sunlight.

Keep away from oxidising agents and acidic substances.

Freezing conditions

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide
- · Additional information: Hazardous decomposition products may form during combustion.

* 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
ATE (Acu	ATE (Acute Toxicity Estimate)		
Oral	LD50	165,000 mg/kg (rat)	
Dermal	LD50	30,000 mg/kg	
Inhalative	LC50/4 h	16.2 mg/l (rat)	

80-62-6 m	80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	18 mg/l (rat)	
99-97-8 N	99-97-8 N,N-dimethyl-p-toluidine		
Oral	LD50	1,650 mg/kg (rat)	
Dermal	LD50	300 mg/kg (ATE)	
Inhalative	LC50/4 h	1.4 mg/l (rat)	

- · Primary chemical irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (I	nternational Agency for Research on Cancer)	
80-62-6	methyl methacrylate	3
99-97-8	N,N-dimethyl-p-toluidine	2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: Acrylic Tinting Concentrate

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic tox	icity:
80-62-6 met	hyl methacrylate
EC50 (96 h)	170 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)	69 mg/l (daphnia)
LC50 (96 h)	79 mg/l (oncorhynchus mykiss)
99-97-8 N,N	-dimethyl-p-toluidine
LC50 (96 h)	46 mg/l (pimephales promelas)

- · Persistence and degradability Not easily biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil Potential for mobility in soil is very high.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN1247
UN proper shipping nameDOTIMDG, IATA	Methyl methacrylate monomer, stabilized METHYL METHACRYLATE MONOMER, STABILIZED
. Transport hazard class(as)	

· Transport hazard class(es)

· DOT



· Class
· Label

3 Flammable liquids
3

(Contd. on page 8)

Product name: Acrylic Tinting Concentrate

(Contd. of page 7)

3 Flammable liquids
3
II
No
Warning: Flammable liquids
33
F-E,S-D
C
SW1 Protected from sources of heat.
SW2 Clear of living quarters.
73/78 and
Not applicable.
On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L
1L
2 D/E
D/E
17
1L Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per niner packaging: 50 ml
UN 1247 METHYL METHACRYLATE MONOMER,
STABILIZED, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara
Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

· TSCA (Toxic Substances Control Act):

All other ingredients are exempt from listing.

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 methyl methacrylate

(Contd. on page 9)

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: Acrylic Tinting Concentrate

(Contd. of page 8)

· Proposition 65

· Chemicals known to cause cancer:

99-97-8 N,N-dimethyl-p-toluidine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Services
- · Contact: Pablo Mendoza
- · Last revision / supersedes version: 06/01/2022 / 4.1
- · **Supersedes date:** 04/26/2022
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 4: Flammable liquids - Category 4

Acute Toxicity - Oral 3: Acute toxicity - Category 3 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Sensitization - Skin 1: Skin sensitisation - Category 1

Carcinogenicity 2: Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.