

Page 1/9

Safety Data Sheet acc. to OSHA HCS

1 Identification

· Product name: PurpleLube Polishing Lubricant

· Part number: 90-204995, 90-205000, 90-205005, 90-205010

· Application of the substance / the mixture Lubricant

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:
 Allied High Tech Products Inc.
 2376 East Pacifica Place
 USA-RANCHO DOMINGUEZ, CA 90220
 USA

info@alliedhightech.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (310) 635-2466

Chemtrec: +1 (202) 483-7616

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: isopropyl alcohol
- · **Hazard statements** Highly flammable liquid and vapor.

(Contd. on page 2)

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

(Contd. of page 1)

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardo	ous components and components with occupational exposure limits:	
64-17-5	ethyl alcohol	60-70%
	🏇 Flammable Liquids 2, H225	
57-55-6	propylene glycol	10-20%
67-63-0	isopropyl alcohol	10-<20%
	Flammable Liquids 2, H225; Eye Irritation 2A, H319; Specific Target Organ Toxicity - Single Exposure 3, H336	

Additional information: The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eve contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Gastric or intestinal disorders

Disorientation

Unconsciousness

Headache

Dizziness

Nausea

Eve irritation

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 3)

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

No special requirements.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

64-17-5 ethyl alcohol

PEL Long-term value: 1900 mg/m³, 1000 ppm

Version 5.0 Printing date 06/01/2022 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

	(Contd. of page 3)
REL	Long-term value: 1900 mg/m³, 1000 ppm
TLV	Short-term value: 1000 ppm
	A3
57-55-0	6 propylene glycol
WEEL	Long-term value: 10 mg/m³
67-63-0) isopropyl alcohol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm
	Long-term value: 200 ppm
	BEI, A4

Ingredients with biological limit values:

67-63-0 isopropyl alcohol

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use suitable respiratory protective device when high concentrations are present.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Violet Color:

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

	(Contd. of page
· Odor: · Odor threshold:	Alcohol-like Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 78 °C (172.4 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	3.5 Vol % 15 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
 Density at 20 °C (68 °F): Relative density Vapor density Specific gravity: Evaporation rate 	0.826 g/cm³ (6.893 lbs/gal) Not determined. 1.5 0.8 (Water = 1) Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water	er): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC content:	100.0 % 100.00 %
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid

Keep away from heat.

Keep away from oxidising agents and acidic substances.

Keep away from open flames. - No smoking.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide
- · Additional information: Hazardous decomposition products may form during combustion.

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

(Contd. of page 5)

* 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:								
Oral	LD50	>5,000 mg/kg (rat)							
64-17-5 et	64-17-5 ethyl alcohol								
Oral	LD50	7,060 mg/kg (rat)							
Dermal	LD50	15,800 mg/kg (rabbit)							
Inhalative	LC50/4 h	20,000 mg/l (rat)							
57-55-6 pi	opylene g	lycol							
Oral	ral LD50 >2,000 mg/kg (rat)								
Dermal	Dermal LD50 20,800 mg/kg (rabbit)								
67-63-0 is	67-63-0 isopropyl alcohol								
Oral	ral LD50 5,045 mg/kg (rat)								
Dermal	LD50	12,800 mg/kg (rabbit)							
Inhalative	Inhalative LC50/4 h 30 mg/l (rat)								

- Primary chemical irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Specific Target Organ Toxicity - Single Exposure 3 - Target Organ: central nervous system depression

· Carcinogenic categories

Carcino	ogenic categories					
· IARC (International Agency for Research on Cancer)					
64-17-5	ethyl alcohol	1				
67-63-0	isopropyl alcohol	3				
· NTP (N	· NTP (National Toxicology Program)					
None of	None of the ingredients is listed.					
· OSHA-	· OSHA-Ca (Occupational Safety & Health Administration)					
None of	None of the ingredients is listed.					

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)

Product name: PurpleLube Polishing Lubricant

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Contact waste processors for recycling information.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1	4	T	ra	n	S	D	0	rt	i	n	fa) <i>I</i>	n	ı	a	i	o)/	ı

· Transport category

UNI Namelan	
· UN-Number · DOT, IMDG, IATA	UN1987
	01(1)07
· UN proper shipping name · DOT	Alcohols, n.o.s. (Ethanol, Isopropanol)
IMDG	Alcohols, n.o.s. (Edianol, Isopropanol) ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL),
IMDG	ISOPROPANOL (ISOPROPYL ALCOHOL))
· IATA	ALCOHOLS, N.O.S. (ETHANOL, ISOPROPANOL (ISOPROPYL
	ALCOHOL))
· Transport hazard class(es)	
· DOT	
PLOMINEE CUUC	
· Class	3 Flammable liquids
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
·Label	3
· Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	В
Transport in bulk according to Annex II of MARPOL7	73/78 and
the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
- v	On cargo aircraft only: 60 L
· Limited quantities (LQ)	1L
	2

2

Printing date 06/01/2022 Version 5.0 Last revision 06/01/2022

Product name: PurpleLube Polishing Lubricant

(Contd. of page 7)

· Tunnel restriction code	D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL), ISOPROPANOL (ISOPROPYL ALCOHOL)), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

	· Section 355 (extremely hazardous substances):
	None of the ingredients is listed.
Ē	· Section 313 (Specific toxic chemical listings):

67-63-0 isopropyl alcohol

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

64-17-5 ethyl alcohol

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Services
- · Contact: Pablo Mendoza
- · Last revision / supersedes version: 06/01/2022 / 4.1
- · Supersedes date: 06/03/2020
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Version 5.0 Printing date 06/01/2022 *Last revision 06/01/2022*

Product name: PurpleLube Polishing Lubricant

(Contd. of page 8)

OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit
Flammable Liquids 2: Flammable liquids – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.