

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

1 Identification

- **Product name:** Mounting Wax, Hot
- **Part number:** 71-10040, 71-10050
- **Application of the substance / the mixture** Adhesives
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Allied High Tech Products Inc.
2376 East Pacifica Place
USA-RANCHO DOMINGUEZ, CA 90220
USA
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (310) 635-2466
Chemtrec: +1 (202) 483-7616

*** 2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 1)

Hazard pictograms

GHS05 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

phthalic anhydride

Hazard statements

Causes skin irritation.

Causes serious eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

* 3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:** Mixture of the substances listed below with nonhazardous additions.**Hazardous components and components with occupational exposure limits:**

85-44-9	phthalic anhydride	50-100%
	⚠ Resp. Sens. 1, H334; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
107-21-1	ethylene glycol	25-50%
	⚠ Acute Tox. 4, H302	

Additional information: The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

* 4 First-aid measures

Description of first aid measures**General information:** Immediately remove any clothing soiled by the product.**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
Breathing difficulty
Coughing
Allergic reactions
Dermatitis
Eye irritation
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Suitable material for receptacles and pipes: steel or stainless steel.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:	
85-44-9 phthalic anhydride	
PEL	Long-term value: 12 mg/m ³ , 2 ppm
REL	Long-term value: 6 mg/m ³ , 1 ppm
TLV	Short-term value: 0.005* mg/m ³ , 0.0009* ppm Long-term value: 0.002* mg/m ³ , 0.0003* ppm *inhalable&vapor; Skin; DSEN, RSEN

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 3)

107-21-1 ethylene glycol	
TLV	Short-term value: 10** mg/m ³ , 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only
WEEL	I (2)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Solid
Color:	Clear
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not applicable.
· Change in condition	
Melting point/Melting range:	68-74 °C (154.4-101.2 °F)
Boiling point/Boiling range:	>100 °C (>212 °F)
· Flash point:	>263 °C (>505.4 °F)
· Flammability (solid, gaseous):	Not determined.
· Ignition temperature:	580 °C (1,076 °F)
· Decomposition temperature:	Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 4)

· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	1.7 Vol %
Upper:	10.5 Vol %
· Vapor pressure:	Not applicable.
· Density at 20 °C (68 °F):	1.435 g/cm ³ (11.975 lbs/gal)
· Relative density	Not determined.
· Vapor density	>1.0
· Specific gravity:	1.31
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC content:	30.77 %
Solids content:	69.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Keep away from heat.
Keep away from open flames. - No smoking.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide
- **Additional information:** Hazardous decomposition products may form during combustion.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	6,067 mg/kg (rat)
85-44-9 phthalic anhydride		
Oral	LD50	4,200 mg/kg (rat)
107-21-1 ethylene glycol		
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	9,430 mg/kg (rabbit)

- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 5)

- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.
· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es) · DOT, ADN, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 6)

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	not regulated

*15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):
None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):
All ingredients are listed.

· TSCA (Toxic Substances Control Act):
All components have the value ACTIVE.

· Hazardous Air Pollutants
All ingredients are listed.

- **Proposition 65**

· Chemicals known to cause cancer:
None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:
107-21-1 ethylene glycol

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Kim Dermit
- **Last revision / supersedes version:** 06/04/2020 / 2.0
- **Supersedes date:** 05/01/2020
- **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/04/2020

Version 2.1

Last revision 06/04/2020

Product name: Mounting Wax, Hot

(Contd. of page 7)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**