

## Safety Data Sheet acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

### \* 1 Identification

- **Product name:** Phenolic Mounting Powder - Red, Black, Green
- **Part number:** 135-10005, 135-10007, 135-10010, 135-10012, 135-10015, 135-10017, Preforms
- **Application of the substance / the mixture** Thermoset molding
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
16207 Carmenita Road  
USA-Cerritos, CA, 90703  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Germ Cell Mutagenicity 2	H341 Suspected of causing genetic defects.
Carcinogenicity 2	H351 Suspected of causing cancer.
Specific Target Organ Toxicity - Repeated Exposure 2	H373 May cause damage to the central nervous system, the kidneys, the liver, the heart and the respiratory system through prolonged or repeated exposure.



GHS07

Skin Irritation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Sensitization - Skin 1	H317 May cause an allergic skin reaction.

Combustible Dust	May form combustible dust concentrations in air.
------------------	--

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 1)

**· Hazard pictograms**

GHS07 GHS08

**· Signal word** Warning**· Hazard-determining components of labeling:**

methenamine

Carbon black

phenol

**· Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

Suspected of causing cancer.

May cause damage to the central nervous system, the kidneys, the liver, the heart and the respiratory system through prolonged or repeated exposure.

May form combustible dust concentrations in air.

**· Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### \* 3 Composition/information on ingredients

**· Chemical characterization: Mixtures****· Description:** Mixture of the substances listed below with nonhazardous additions.**· Hazardous components and components with occupational exposure limits:**

12001-26-2	Mica	0-60%
	Wood flour	0-60%
1332-58-7	Kaolin	0-40%
7782-42-5	Graphite	0-40%
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	0-20%
	Coal dust	0-18%
100-97-0	methenamine	2-15%

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 2)

1333-86-4	Carbon black ⚠ Self-heating substances and mixtures 2, H252; ⚠ Carcinogenicity 2, H351	0-12%
1305-62-0	calcium dihydroxide ⚠ Skin Corrosion 1B, H314; Eye Damage 1, H318	0-10%
108-95-2	phenol ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ⚠ Germ Cell Mutagenicity 2, H341; Specific Target Organ Toxicity - Repeated Exposure 2, H373; ⚠ Skin Corrosion 1B, H314	<3.5%
50-00-0	formaldehyde ⚠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ⚠ Germ Cell Mutagenicity 2, H341; Carcinogenicity 1A, H350; ⚠ Skin Corrosion 1B, H314; ⚠ Sensitization - Skin 1, H317; Flammable Liquids 4, H227	<0.1%

· **Non-hazardous components:**

9003-35-4	Phenolic Polymer	30-60%
-----------	------------------	--------

· **Additional information:** The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Coughing

Allergic reactions

Dermatitis

Eye irritation

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Keep away from ignition sources

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

# Safety Data Sheet

*acc. to OSHA HCS*

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

Product name: Phenolic Mounting Powder - Red, Black, Green

(Contd. of page 3)

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure proper ventilation/exhaustion at workplaces.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store at temperatures not exceeding 30°C.  
Store only in the original receptacle.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No additional data. See 7.
- **Control parameters**

· <b>Components with limit values that require monitoring at the workplace:</b>
---

<b>12001-26-2 Mica</b>	
PEL	Long-term value: 20 mppcf ppm <1% crystalline silica
REL	Long-term value: 3* mg/m <sup>3</sup> *respirable dust; containing < 1% quartz
TLV	Long-term value: 0.1 mg/m <sup>3</sup> *Respirable particulate matter
<b>Wood flour</b>	
PEL	Long-term value: 15 mg/m <sup>3</sup>
<b>1332-58-7 Kaolin</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 2* mg/m <sup>3</sup> E; respirable particulate matter, A4
<b>7782-42-5 Graphite</b>	
PEL	Long-term value: 15 mppcf* mg/m <sup>3</sup> *impinger samples counted by light field techn.
REL	Long-term value: 2.5* mg/m <sup>3</sup> *respirable dust
TLV	Long-term value: 2* mg/m <sup>3</sup> all forms except graphite fibers;*resp. fraction
<b>14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)</b>	
PEL	Long-term value: 20 mppcf ppm (containing <1% Quartz)

(Contd. on page 5)

## Safety Data Sheet

*acc. to OSHA HCS*

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 4)

REL	Long-term value: 2* mg/m <sup>3</sup> *respirable dust; and <1% Quartz
TLV	Long-term value: 2* mg/m <sup>3</sup> *no asbestos fibers, resp. particulate matter, E, A4
<b>Coal dust</b>	
PEL	Long-term value: 10 mg/m <sup>3</sup>
<b>100-97-0 methenamine</b>	
TLV	Long-term value: 1 mg/m <sup>3</sup> *inhalable fraction, A4, DSEN
<b>1333-86-4 Carbon black</b>	
PEL	Long-term value: 3.5 mg/m <sup>3</sup>
REL	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps. A+C
TLV	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction, A3
<b>1305-62-0 calcium dihydroxide</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 5 mg/m <sup>3</sup>
TLV	Long-term value: 5 mg/m <sup>3</sup>
<b>108-95-2 phenol</b>	
PEL	Long-term value: 19 mg/m <sup>3</sup> , 5 ppm Skin
REL	Long-term value: 19 mg/m <sup>3</sup> , 5 ppm Ceiling limit value: 60* mg/m <sup>3</sup> , 15.6* ppm *15-min; Skin
TLV	Long-term value: 5 ppm Skin; BEI, A4
<b>50-00-0 formaldehyde</b>	
PEL	Short-term value: 2 ppm Long-term value: 0.75 ppm see 29 CFR 1910.1048(c)
REL	Long-term value: 0.016 ppm Ceiling limit value: 0.1* ppm *15-min; See Pocket Guide App. A
TLV	Short-term value: 0.3 ppm Long-term value: 0.1 ppm DSEN; RSEN, A1
<b>· Ingredients with biological limit values:</b>	
<b>108-95-2 phenol</b>	
BEI	250 mg/g creatinine Medium: urine Time: end of shift Parameter: Phenol with hydrolysis (background, nonspecific)

**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 5)

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· <b>Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
<b>Form:</b>	Powder
<b>Color:</b>	According to product specification
· <b>Odor:</b>	Phenol-like
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not applicable.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	Undetermined.
· <b>Flash point:</b>	Not applicable.
· <b>Flammability (solid, gaseous):</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Dust 0.03 oz per cubic foot
<b>Upper:</b>	Not determined.
· <b>Vapor pressure:</b>	Not applicable.
· <b>Density at 20 °C (68 °F):</b>	0.6 g/cm <sup>3</sup> (5.007 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not applicable.
· <b>Specific gravity at 20 °C (68 °F):</b>	1.39 g/cm <sup>3</sup> (11.6 lbs/gal)
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Insoluble.

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

Product name: Phenolic Mounting Powder - Red, Black, Green

(Contd. of page 6)

· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	1.1 %
<b>VOC content:</b>	1.06 %
<b>Solids content:</b>	100.0 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**  
Keep away from oxidising agents and acidic substances.  
Keep away from heat.  
Keep away from open flames. - No smoking.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Formaldehyde  
Phenol  
Ammonia
- **Additional information:** Hazardous decomposition products may form during combustion.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
<b>1333-86-4 Carbon black</b>		
Oral	LD50	10,000 mg/kg (rat)
<b>1305-62-0 calcium dihydroxide</b>		
Oral	LD50	7,340 mg/kg (rat)
<b>108-95-2 phenol</b>		
Oral	LD50	317 mg/kg (rat)
Dermal	LD50	850 mg/kg (rabbit)
Inhalative	LC50/4 h	0.5 mg/l (ATE)
<b>50-00-0 formaldehyde</b>		
Oral	LD50	>200 mg/kg (rat)
Dermal	LD50	270 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 8)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 7)

- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
1333-86-4	Carbon black	2B
108-95-2	phenol	3
50-00-0	formaldehyde	1
· NTP (National Toxicology Program)		
50-00-0	formaldehyde	K
· OSHA-Ca (Occupational Safety & Health Administration)		
50-00-0	formaldehyde	

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b> · <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>UN proper shipping name</b> · <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>Transport hazard class(es)</b> · <b>DOT, IMDG, IATA</b> · <b>Class</b> · <b>Label</b> · <b>ADN/R Class:</b>	not regulated - not regulated
· <b>Packing group</b> · <b>DOT, IMDG, IATA</b>	not regulated

(Contd. on page 9)

# Safety Data Sheet

*acc. to OSHA HCS*

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 8)

· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	not regulated

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· <b>Section 355 (extremely hazardous substances):</b>	
108-95-2	phenol
50-00-0	formaldehyde

· <b>Section 313 (Specific toxic chemical listings):</b>	
108-95-2	phenol
50-00-0	formaldehyde

- **TSCA (Toxic Substances Control Act):**  
All other ingredients are exempt from listing.

9003-35-4	Phenolic Polymer	ACTIVE
1332-58-7	Kaolin	ACTIVE
7782-42-5	Graphite	ACTIVE
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	ACTIVE
100-97-0	methenamine	ACTIVE
1333-86-4	Carbon black	ACTIVE
1305-62-0	calcium dihydroxide	ACTIVE
108-95-2	phenol	ACTIVE
50-00-0	formaldehyde	ACTIVE

· <b>Hazardous Air Pollutants</b>	
108-95-2	phenol
50-00-0	formaldehyde

- **Proposition 65**

· <b>Chemicals known to cause cancer:</b>	
1333-86-4	Carbon black
50-00-0	formaldehyde

· <b>Chemicals known to cause reproductive toxicity for females:</b>	
None of the ingredients is listed.	

· <b>Chemicals known to cause reproductive toxicity for males:</b>	
None of the ingredients is listed.	

· <b>Chemicals known to cause developmental toxicity:</b>	
None of the ingredients is listed.	

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

To the best of our knowledge, the information contained herein is accurate. However, it does not describe a guarantee of product properties and does not establish a contractual legal relationship.

- **Department issuing SDS:** Technical Services

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/02/2024

Version 6.0

Last revision 06/01/2024

**Product name: Phenolic Mounting Powder - Red, Black, Green**

(Contd. of page 9)

- **Contact:** Pablo Mendoza

- **Last revision / supersedes version:** 06/01/2024 / 5.0

- **Supersedes date:** 06/01/2022

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4

Flammable Solids 2: Flammable solids – Category 2

Self-heating substances and mixtures 2: Self-heating substances and mixtures – Category 2

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Germ Cell Mutagenicity 2: Germ cell mutagenicity – Category 2

Carcinogenicity 1A: Carcinogenicity – Category 1A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

- **\* Data compared to the previous version altered.**