

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

### 1 Identification

- **Product name:** QuickSet Acrylic Liquid
- **Part number:** 185-10000, 185-10015, 185-10010, 185-10025, 185-10035, 185-10036
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
2376 East Pacifica Place  
USA-RANCHO DOMINGUEZ, CA 90220  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

### \* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3

H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning

(Contd. on page 2)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 1)

- **Hazard-determining components of labeling:**

isobutyl methacrylate

- **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Hazardous components and components with occupational exposure limits:**

97-86-9	isobutyl methacrylate	80-90%
	⚠ Flammable Liquids 3, H226; ⚠ Skin Irritation 2, H315; Sensitization - Skin 1B, H317; Specific Target Organ Toxicity - Single Exposure 3, H335	
3290-92-4	propylidyntrimethyl trimethacrylate	10-20%

- **Additional information:** The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

### \* 4 First-aid measures

- **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
  - Headache
  - Dizziness
  - Allergic reactions
  - Nausea
  - Dermatitis
  - Eye irritation
- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### \* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:**
  - Water spray
  - Water with full jet
- **Special hazards arising from the substance or mixture**
  - Vapor forms an explosive mixture with air.
  - Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.
  - This product is flammable liquid.
  - Closed containers may rupture or explode during a runaway polymerization.
  - For bulk size >1L - High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure.
- **Advice for firefighters**
- **Protective equipment:**
  - Wear self-contained respiratory protective device.
  - Wear fully protective suit.
- **Additional information** Cool endangered receptacles with water spray.

### \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation
  - Keep away from ignition sources
- **Environmental precautions:**
  - ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
  - Do not allow product to reach sewage system or any water course.
  - Do not allow to enter sewers/ surface or ground water.
  - Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
  - Warm water and cleansing agent
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Dispose contaminated material as waste according to item 13.
  - Ensure adequate ventilation.
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

### \* 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
  - Keep receptacles tightly sealed.
  - Keep away from heat and direct sunlight.
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.

(Contd. on page 4)

# Safety Data Sheet

*acc. to OSHA HCS*

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 3)

- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Protect from sunlight.
- **Information about storage in one common storage facility:** Store away from heat.
- **Further information about storage conditions:**  
Store at temperatures not exceeding 30°C.  
Keep receptacle tightly sealed.  
Store receptacle in a well ventilated area.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

3290-92-4 propylidynetrimehyl trimethacrylate	
WEEL	Long-term value: 1 mg/m <sup>3</sup> Skin

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
Butyl rubber, BR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

Product name: QuickSet Acrylic Liquid

(Contd. of page 4)

### \* 9 Physical and chemical properties

· <b>Information on basic physical and chemical properties</b>	
· <b>General Information</b>	
· <b>Appearance:</b>	
Form:	Liquid
Color:	Yellow
· <b>Odor:</b>	Acrid
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	155 °C (311 °F)
· <b>Flash point:</b>	46 °C (114.8 °F) (closed cup)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	390 °C (734 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	1 Vol %
Upper:	8 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	4 hPa (3 mm Hg)
· <b>Density:</b>	Not determined.
· <b>Relative density</b>	Not determined.
· <b>Vapor density at 16 °C (60.8 °F)</b>	4.91 (Air = 1)
· <b>Specific gravity at 20 °C (68 °F):</b>	0.913
· <b>Evaporation rate</b>	0.5
· <b>Solubility in / Miscibility with</b>	
Water:	0.47 g/l
· <b>Partition coefficient (n-octanol/water):</b> 2.95 log POW	
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
VOC content:	0.00 %
Solids content:	15.0 %
· <b>Other information</b>	No further relevant information available.

### \* 10 Stability and reactivity

- **Reactivity** Unstable/Reactive upon depletion of inhibitor.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Danger of polymerization.
- **Conditions to avoid**  
Keep away from alkaline solutions.  
Keep away from oxidising agents and acidic substances.  
Protect from sunlight.

(Contd. on page 6)

# Safety Data Sheet

*acc. to OSHA HCS*

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 5)

Keep away from heat.

- **Incompatible materials:**

Inert gases

Oxygen scavengers

Strong reducing agents

Free-radical generators

Strong oxidizing agents

- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

- **Additional information:** Hazardous decomposition products may form during combustion.

## \* 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary chemical irritant effect:**

- **on the skin:**

May be harmful in contact with skin.

Irritant to skin and mucous membranes.

- **on the eye:**

Causes severe eye irritation.

Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>
None of the ingredients is listed.

· <b>NTP (National Toxicology Program)</b>
None of the ingredients is listed.

· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>
None of the ingredients is listed.

## \* 12 Ecological information

- **Toxicity**

· <b>Aquatic toxicity:</b>
EC50 (96 h)   0.29 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)   >23 mg/l (daphnia)
LC50 (96 h)   20 mg/l (rainbow trout)

<b>97-86-9 isobutyl methacrylate</b>
EC50 (96 h)   0.29 mg/l (pseudokirchneriella subcapitata)
EC50 (48 h)   >23 mg/l (daphnia)
LC50 (96 h)   20 mg/l (rainbow trout)

- **Persistence and degradability** Easily biodegradable

- **Behavior in environmental systems:**

- **Bioaccumulative potential** May be accumulated in organism

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 6)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## \*13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must be specially treated adhering to official regulations.  
Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	UN1993
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	Flammable liquids, n.o.s. FLAMMABLE LIQUID, N.O.S.
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> </ul>	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	3 Flammable liquids 3
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>	III
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>	Yes
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	Warning: Flammable liquids 30 F-E, <u>S-E</u> E
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	Not applicable.
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Transport category</b></li> </ul>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L 5L 3

(Contd. on page 8)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 7)

· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

### 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Technical Services

· **Contact:** Pablo Mendoza

· **Last revision / supersedes version:** 06/08/2022 / 3.0

· **Supersedes date:** 03/15/2021

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 9)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 06/08/2022

Version 4.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Liquid**

(Contd. of page 8)

REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Sensitization - Skin 1B: Skin sensitisation – Category 1B

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· **\* Data compared to the previous version altered.**

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**1 Identification**

- **Product name:** QuickSet Acrylic Powder
- **Part number:** 185-10000, 185-10015, 185-10005, 185-10020, 185-10030, 185-10040
- **Application of the substance / the mixture** Acrylic resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Allied High Tech Products Inc.  
2376 East Pacifica Place  
USA-RANCHO DOMINGUEZ, CA 90220  
USA  
info@alliedhightech.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (310) 635-2466  
Chemtrec: +1 (202) 483-7616

**\* 2 Hazard(s) identification**

- **Classification of the substance or mixture**



Skin Irritation 2      H315 Causes skin irritation.  
Sensitization - Skin 1    H317 May cause an allergic skin reaction.  
Eye Irritation 2B      H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Warning
- **Hazard-determining components of labeling:**  
dibenzoyl peroxide
- **Hazard statements**  
Causes skin and eye irritation.  
May cause an allergic skin reaction.
- **Precautionary statements**  
Avoid breathing dust/fume/gas/mist/vapors/spray

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Powder**

(Contd. of page 1)

- Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.  
 Wear protective gloves.  
 If on skin: Wash with plenty of water.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Specific treatment (see on this label).  
 If eye irritation persists: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· <b>Hazardous components and components with occupational exposure limits:</b>		
9003-42-3	Poly(ethyl methacrylate) ⚠ Skin Irritation 2, H315; Eye Irritation 2A, H319	90-100%
94-36-0	dibenzoyl peroxide ⚠ Organic Peroxides - Type B, H241; ⚠ Eye Irritation 2A, H319; Sensitization - Skin 1, H317	1-5%

- **Additional information:** The specific chemical identity and/or exact percentage of the composition has been withheld as a trade secret.

### \* 4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
Eye irritation  
Allergic reactions  
Dermatitis  
Eye irritation  
Dermatitis
- **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### \* 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
For bulk size: Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Remove any contaminated clothing and wash thoroughly before reuse.
- **Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Powder**

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material, sand or earth.  
Sweep up to avoid slipping hazard.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### \* 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Wash hands and other exposed areas after use.  
Avoid contact with skin, eyes or clothing.  
Avoid breathing dust or fume.  
Handle in accordance with good industrial hygiene and safety practice.  
Ensure good ventilation/exhaustion at the workplace.

- **Information about protection against explosions and fires:** No special measures required.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store in a dry place. Store in a closed container.  
Protect from sunlight.  
Store at temperatures not exceeding 35°C.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.  
Store receptacle in a well ventilated area.

- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

94-36-0 dibenzoyl peroxide	
IDLH	Long-term value: 5 mg/m <sup>3</sup>
PEL	Long-term value: 5 mg/m <sup>3</sup>
TLV	Long-term value: 5 mg/m <sup>3</sup>
	A4

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

- **Breathing equipment:** Use suitable respiratory protective device when high concentrations are present.

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Powder**

(Contd. of page 3)

**Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Eye protection:**

Tightly sealed goggles

### \* 9 Physical and chemical properties

**Information on basic physical and chemical properties****General Information****Appearance:****Form:** Powder**Color:** White**Odor:** Faint odor in bulk**Odor threshold:** Not determined.**pH-value:** Not applicable.**Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** Undetermined.**Flash point:** 303 °C (577.4 °F)**Flammability (solid, gaseous):** Not determined.**Decomposition temperature:** Not determined.**Auto igniting:** 80 °C (176 °F)**Danger of explosion:** Product does not present an explosion hazard.**Explosion limits:****Lower:** Not determined.**Upper:** Not determined.**Vapor pressure:** Not applicable.**Density:** Not determined.**Relative density** Not determined.**Vapor density** Not applicable.**Specific gravity at 20 °C (68 °F):** 0 g/cm<sup>3</sup>**Evaporation rate** Not applicable.**Solubility in / Miscibility with****Water:** Insoluble.**Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

Product name: QuickSet Acrylic Powder

(Contd. of page 4)

· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not applicable.
<b>Kinematic:</b>	Not applicable.
· <b>Solvent content:</b>	
<b>VOC content:</b>	0.00 %
<b>Solids content:</b>	100.0 %
· <b>Other information</b>	No further relevant information available.

## \* 10 Stability and reactivity

- **Reactivity** Not reactive under normal conditions.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Strong oxidizing agents
- **Hazardous decomposition products:**  
Methacrylate monomers  
Carbon monoxide and carbon dioxide
- **Additional information:** Hazardous decomposition products may form during combustion.

## \* 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary chemical irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
Abrasive skin irritant  
Abrasive eye irritant
- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
94-36-0	dibenzoyl peroxide	3
· <b>NTP (National Toxicology Program)</b>		
None of the ingredients is listed.		
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Powder**

(Contd. of page 5)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b>	
· <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>UN proper shipping name</b>	
· <b>DOT, ADN, IMDG, IATA</b>	not regulated
· <b>Transport hazard class(es)</b>	
· <b>DOT, ADN, IMDG, IATA</b>	
· <b>Class</b>	not regulated
· <b>Packing group</b>	
· <b>DOT, IMDG, IATA</b>	not regulated
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	not regulated

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **Sara**

· <b>Section 355 (extremely hazardous substances):</b>	None of the ingredients is listed.
· <b>Section 313 (Specific toxic chemical listings):</b>	94-36-0   dibenzoyl peroxide
· <b>TSCA (Toxic Substances Control Act):</b>	All components have the value ACTIVE.
· <b>Hazardous Air Pollutants</b>	None of the ingredients is listed.
· <b>Proposition 65</b>	
· <b>Chemicals known to cause cancer:</b>	None of the ingredients is listed.
· <b>Chemicals known to cause reproductive toxicity for females:</b>	None of the ingredients is listed.
· <b>Chemicals known to cause reproductive toxicity for males:</b>	None of the ingredients is listed.

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/08/2022

Version 5.0

Last revision 06/08/2022

**Product name: QuickSet Acrylic Powder**

(Contd. of page 6)

<b>· Chemicals known to cause developmental toxicity:</b>
None of the ingredients is listed.
<b>· Chemical safety assessment:</b> A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Technical Services

- **Contact:** Pablo Mendoza

- **Last revision / supersedes version:** 06/08/2022 / 4.0

- **Supersedes date:** 4/27/2020

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Organic Peroxides - Type B: Organic peroxides – Type B

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Eye Irritation 2B: Serious eye damage/eye irritation – Category 2B

Sensitization - Skin 1: Skin sensitisation – Category 1

- **\* Data compared to the previous version altered.**